




# Model HX0036 Duplex Pump Set



The type X system is provided as a complete mechanical assembly with all piping complete as shown. Unit will be hydrostatically tested and fluorescent leak inspected at the factory. The system requires wiring and controls by others.

## Performance Data & Equipment Information

Pump Flow Rate (gph)	36	Motor HP	1/3	Volts *	115	Inlet conn. size	1/2"
Discharge Press. (psig)	100	RPM	1750	Phase	1	Outlet conn. size	1/2"
Estimated System Weight (lbs.)	300			Motor Full Load Amps @ 115 Volts *	7.2		

\* All standard single and three phase voltage available upon request.




## Standard Equipment

(2) pumps, (2) ODP motors, (2) permanent alignment brackets with flexible couplings, (2) simplex inlet basket strainers, 1/16" perforated baskets, (2) inlet full port ball valves, (2) 2 1/2" SS case, liquid filled compound gauge with shut-off cock, (2) external relief valves, (2) outlet full port ball valves, (2) check valves, (1) 2 1/2" SS case, liquid filled pressure gauge with shut-off cock. All equipment mounted on formed steel unit base with drip pan.

## System Options: Check all that apply

Rupture basin leak switch		4" SS liquid filled gauge ILO 2 1/2"	
Duplex Strainer ILO (2) Simplex		Gauge snubber	
Strainer DP switch/indicator		TEFC motors	
Discharge flow switch		Flex hose conn (suc/disch)	
Discharge pressure switch		Unit vibration isolation mounts	

# Model HX0081 Duplex Pump Set



The type X system is provided as a complete mechanical assembly with all piping complete as shown. Unit will be hydrostatically tested and fluorescent leak inspected at the factory. The system requires wiring and controls by others.

### Performance Data & Equipment Information

Pump Flow Rate (gph)	81	Motor HP	1/3	Volts *	115	Inlet conn. size	1/2"
Discharge Press. (psig)	100	RPM	1750	Phase	1	Outlet conn. size	1/2"
Estimated System Weight (lbs.)			300	Motor Full Load Amps @ 115 Volts *		7.2	

\* All standard single and three phase voltage available upon request.




### Standard Equipment

(2) pumps, (2) ODP motors, (2) permanent alignment brackets with flexible couplings, (2) simplex inlet basket strainers, 1/16" perforated baskets, (2) inlet full port ball valves, (2) 2 1/2" SS case, liquid filled compound gauge with shut-off cock, (2) external relief valves, (2) outlet full port ball valves, (2) check valves, (1) 2 1/2" SS case, liquid filled pressure gauge with shut-off cock. All equipment mounted on formed steel unit base with drip pan.

### System Options: Check all that apply

Rupture basin leak switch		4" SS liquid filled gauge ILO 2 1/2"	
Duplex Strainer ILO (2) Simplex		Gauge snubber	
Strainer DP switch/indicator		TEFC motors	
Discharge flow switch		Flex hose conn (suc/disch)	
Discharge pressure switch		Unit vibration isolation mounts	

# Model HX0156 Duplex Pump Set



The type X system is provided as a complete mechanical assembly with all piping complete as shown. Unit will be hydrostatically tested and fluorescent leak inspected at the factory. The system requires wiring and controls by others.

## Performance Data & Equipment Information

Pump Flow Rate (gph)	156	Motor HP	1/3	Volts *	115	Inlet conn. size	3/4"
Discharge Press. (psig)	100	RPM	1750	Phase	1	Outlet conn. size	1/2"
Estimated System Weight (lbs.)	300			Motor Full Load Amps @ 115 Volts *	7.2		

\* All standard single and three phase voltage available upon request.




## Standard Equipment

(2) pumps, (2) ODP motors, (2) permanent alignment brackets with flexible couplings, (2) simplex inlet basket strainers, 1/16" perforated baskets, (2) inlet full port ball valves, (2) 2 1/2" SS case, liquid filled compound gauge with shut-off cock, (2) external relief valves, (2) outlet full port ball valves, (2) check valves, (1) 2 1/2" SS case, liquid filled pressure gauge with shut-off cock. All equipment mounted on formed steel unit base with drip pan.

## System Options: Check all that apply

Rupture basin leak switch		4" SS liquid filled gauge ILO 2 1/2"	
Duplex Strainer ILO (2) Simplex		Gauge snubber	
Strainer DP switch/indicator		TEFC motors	
Discharge flow switch		Flex hose conn (suc/disch)	
Discharge pressure switch		Unit vibration isolation mounts	

# Model HX0222 Duplex Pump Set



The type X system is provided as a complete mechanical assembly with all piping complete as shown. Unit will be hydrostatically tested and fluorescent leak inspected at the factory. The system requires wiring and controls by others.

## Performance Data & Equipment Information

Pump Flow Rate (gph)	222	Motor HP	1/3	Volts *	115	Inlet conn. size	3/4"
Discharge Press. (psig)	100	RPM	1750	Phase	1	Outlet conn. size	1/2"
Estimated System Weight (lbs.)	300			Motor Full Load Amps @ 115 Volts *	7.2		

\* All standard single and three phase voltage available upon request.


## Standard Equipment

(2) pumps, (2) ODP motors, (2) permanent alignment brackets with flexible couplings, (2) simplex inlet basket strainers, 1/16" perforated baskets, (2) inlet full port ball valves, (2) 2 1/2" SS case, liquid filled compound gauge with shut-off cock, (2) external relief valves, (2) outlet full port ball valves, (2) check valves, (1) 2 1/2" SS case, liquid filled pressure gauge with shut-off cock. All equipment mounted on formed steel unit base with drip pan.


## System Options: Check all that apply

Rupture basin leak switch		4" SS liquid filled gauge ILO 2 1/2"	
Duplex Strainer ILO (2) Simplex		Gauge snubber	
Strainer DP switch/indicator		TEFC motors	
Discharge flow switch		Flex hose conn (suc/disch)	
Discharge pressure switch		Unit vibration isolation mounts	


# Model HX0300 Duplex Pump Set



Standard with simplex strainer



Options Shown: Duplex Strainer, DP switch,  
 Flow Switch, and Basin Switch



The type X system is provided as a complete mechanical assembly with all piping complete as shown. Unit will be hydrostatically tested and fluorescent leak inspected at the factory. The system requires wiring and controls by others.

## Performance Data & Equipment Information

Pump Flow Rate (gph)	300	Motor HP	1/2	Volts *	460	Inlet conn. size	1"
Discharge Press. (psig)	100	RPM	1750	Phase	3	Outlet conn. size	3/4"
Estimated System Weight (lbs.)	300			Motor Full Load Amps @ 460 Volts *	1.2		

\* All standard single and three phase voltage available upon request.


## Standard Equipment

(2) pumps, (2) ODP motors, (2) permanent alignment brackets with flexible couplings, (2) simplex inlet basket strainers, 1/16" perforated baskets, (2) inlet full port ball valves, (2) 2 1/2" SS case, liquid filled compound gauge with shut-off cock, (2) external relief valves, (2) outlet full port ball valves, (2) check valves, (1) 2 1/2" SS case, liquid filled pressure gauge with shut-off cock. All equipment mounted on formed steel unit base with drip pan.


## System Options: Check all that apply

Rupture basin leak switch		4" SS liquid filled gauge ILO 2 1/2"	
Duplex Strainer ILO (2) Simplex		Gauge snubber	
Strainer DP switch/indicator		TEFC motors	
Discharge flow switch		Flex hose conn (suc/disch)	
Discharge pressure switch		Unit vibration isolation mounts	


# Model HX0412 Duplex Pump Set



Standard with simplex strainer



Options Shown: Duplex Strainer, DP switch,  
 Flow Switch, and Basin Switch



The type X system is provided as a complete mechanical assembly with all piping complete as shown. Unit will be hydrostatically tested and fluorescent leak inspected at the factory. The system requires wiring and controls by others.

## Performance Data & Equipment Information

Pump Flow Rate (gph)	412	Motor HP	3/4	Volts *	460	Inlet conn. size	1"
Discharge Press. (psig)	100	RPM	1150	Phase	3	Outlet conn. size	3/4"
Estimated System Weight (lbs.)	370			Motor Full Load Amps @ 460 Volts *	1.6		

\* All standard single and three phase voltage available upon request.


## Standard Equipment

(2) pumps, (2) ODP motors, (2) permanent alignment brackets with flexible couplings, (2) simplex inlet basket strainers, 1/16" perforated baskets, (2) inlet full port ball valves, (2) 2 1/2" SS case, liquid filled compound gauge with shut-off cock, (2) external relief valves, (2) outlet full port ball valves, (2) check valves, (1) 2 1/2" SS case, liquid filled pressure gauge with shut-off cock. All equipment mounted on formed steel unit base with drip pan.


## System Options: Check all that apply

Rupture basin leak switch		4" SS liquid filled gauge ILO 2 1/2"	
Duplex Strainer ILO (2) Simplex		Gauge snubber	
Strainer DP switch/indicator		TEFC motors	
Discharge flow switch		Flex hose conn (suc/disch)	
Discharge pressure switch		Unit vibration isolation mounts	


# Model HX0540 Duplex Pump Set



Standard with simplex strainer



Options Shown: Duplex Strainer, DP switch,  
 Flow Switch, and Basin Switch



The type X system is provided as a complete mechanical assembly with all piping complete as shown. Unit will be hydrostatically tested and fluorescent leak inspected at the factory. The system requires wiring and controls by others.

## Performance Data & Equipment Information

Pump Flow Rate (gph)	540	Motor HP	1 1/2	Volts *	460	Inlet conn. size	1"
Discharge Press. (psig)	100	RPM	1750	Phase	3	Outlet conn. size	3/4"
Estimated System Weight (lbs.)	390			Motor Full Load Amps @ 460 Volts *	3.0		

\* All standard single and three phase voltage available upon request.


## Standard Equipment

(2) pumps, (2) ODP motors, (2) permanent alignment brackets with flexible couplings, (2) simplex inlet basket strainers, 1/16" perforated baskets, (2) inlet full port ball valves, (2) 2 1/2" SS case, liquid filled compound gauge with shut-off cock, (2) external relief valves, (2) outlet full port ball valves, (2) check valves, (1) 2 1/2" SS case, liquid filled pressure gauge with shut-off cock. All equipment mounted on formed steel unit base with drip pan.


## System Options: Check all that apply

Rupture basin leak switch		4" SS liquid filled gauge ILO 2 1/2"	
Duplex Strainer ILO (2) Simplex		Gauge snubber	
Strainer DP switch/indicator		TEFC motors	
Discharge flow switch		Flex hose conn (suc/disch)	
Discharge pressure switch		Unit vibration isolation mounts	


# Model HX0720 Duplex Pump Set



Standard with simplex strainer  
 Inlet  
 Outlet



Options Shown: Duplex Strainer, DP switch,  
 Flow Switch, and Basin Switch  
 Inlet  
 Outlet



The type X system is provided as a complete mechanical assembly with all piping complete as shown. Unit will be hydrostatically tested and fluorescent leak inspected at the factory. The system requires wiring and controls by others.

## Performance Data & Equipment Information

Pump Flow Rate (gph)	720	Motor HP	1 1/2	Volts *	460	Inlet conn. size	1 1/2"
Discharge Press. (psig)	100	RPM	1150	Phase	3	Outlet conn. size	1 1/4"
Estimated System Weight (lbs.)	530			Motor Full Load Amps @ 460 Volts *	3.0		

\* All standard single and three phase voltage available upon request.

## Standard Equipment


(2) pumps, (2) ODP motors, (2) permanent alignment brackets with flexible couplings, (2) simplex inlet basket strainers, 1/16" perforated baskets, (2) inlet full port ball valves, (2) 2 1/2" SS case, liquid filled compound gauge with shut-off cock, (2) external relief valves, (2) outlet full port ball valves, (2) check valves, (1) 2 1/2" SS case, liquid filled pressure gauge with shut-off cock. All equipment mounted on formed steel unit base with drip pan.

## System Options: Check all that apply


Rupture basin leak switch		4" SS liquid filled gauge ILO 2 1/2"	
Duplex Strainer ILO (2) Simplex		Gauge snubber	
Strainer DP switch/indicator		TEFC motors	
Discharge flow switch		Flex hose conn (suc/disch)	
Discharge pressure switch		Unit vibration isolation mounts	




# Model HX1020 Duplex Pump Set



Standard with simplex strainer



Options Shown: Duplex Strainer, DP switch,  
 Flow Switch, and Basin Switch



The type X system is provided as a complete mechanical assembly with all piping complete as shown. Unit will be hydrostatically tested and fluorescent leak inspected at the factory. The system requires wiring and controls by others.

## Performance Data & Equipment Information

Pump Flow Rate (gph)	1020	Motor HP	2	Volts *	460	Inlet conn. size	1 1/2"
Discharge Press. (psig)	100	RPM	1150	Phase	3	Outlet conn. size	1 1/4"
Estimated System Weight (lbs.)	610			Motor Full Load Amps @ 460 Volts *	3.4		

\* All standard single and three phase voltage available upon request.


## Standard Equipment

(2) pumps, (2) ODP motors, (2) permanent alignment brackets with flexible couplings, (2) simplex inlet basket strainers, 1/16" perforated baskets, (2) inlet full port ball valves, (2) 2 1/2" SS case, liquid filled compound gauge with shut-off cock, (2) external relief valves, (2) outlet full port ball valves, (2) check valves, (1) 2 1/2" SS case, liquid filled pressure gauge with shut-off cock. All equipment mounted on formed steel unit base with drip pan.


## System Options: Check all that apply

Rupture basin leak switch		4" SS liquid filled gauge ILO 2 1/2"	
Duplex Strainer ILO (2) Simplex		Gauge snubber	
Strainer DP switch/indicator		TEFC motors	
Discharge flow switch		Flex hose conn (suc/disch)	
Discharge pressure switch		Unit vibration isolation mounts	


# Model HX1200 Duplex Pump Set



Standard with simplex strainer



Options Shown: Duplex Strainer, DP switch, Flow Switch, and Basin Switch



The type X system is provided as a complete mechanical assembly with all piping complete as shown. Unit will be hydrostatically tested and fluorescent leak inspected at the factory. The system requires wiring and controls by others.

## Performance Data & Equipment Information

Pump Flow Rate (gph)	1200	Motor HP	2	Volts *	460	Inlet conn. size	1 1/2"
Discharge Press. (psig)	100	RPM	1750	Phase	3	Outlet conn. size	1 1/4"
Estimated System Weight (lbs.)	470			Motor Full Load Amps @ 460 Volts *	3.4		

\* All standard single and three phase voltage available upon request.




## Standard Equipment

(2) pumps, (2) ODP motors, (2) permanent alignment brackets with flexible couplings, (2) simplex inlet basket strainers, 1/16" perforated baskets, (2) inlet full port ball valves, (2) 2 1/2" SS case, liquid filled compound gauge with shut-off cock, (2) external relief valves, (2) outlet full port ball valves, (2) check valves, (1) 2 1/2" SS case, liquid filled pressure gauge with shut-off cock. All equipment mounted on formed steel unit base with drip pan.

## System Options: Check all that apply

Rupture basin leak switch		4" SS liquid filled gauge ILO 2 1/2"	
Duplex Strainer ILO (2) Simplex		Gauge snubber	
Strainer DP switch/indicator		TEFC motors	
Discharge flow switch		Flex hose conn (suc/disch)	
Discharge pressure switch		Unit vibration isolation mounts	

# Model HX1680 Duplex Pump Set



The type X system is provided as a complete mechanical assembly with all piping complete as shown. Unit will be hydrostatically tested and fluorescent leak inspected at the factory. The system requires wiring and controls by others.

## Performance Data & Equipment Information

Pump Flow Rate (gph)	1680	Motor HP	3	Volts *	460	Inlet conn. size	2"
Discharge Press. (psig)	100	RPM	1750	Phase	3	Outlet conn. size	1 1/2"
Estimated System Weight (lbs.)	610			Motor Full Load Amps @ 460 Volts *	4.8		

\* All standard single and three phase voltage available upon request.


## Standard Equipment

(2) pumps, (2) ODP motors, (2) permanent alignment brackets with flexible couplings, (2) simplex inlet basket strainers, 1/16" perforated baskets, (2) inlet full port ball valves, (2) 2 1/2" SS case, liquid filled compound gauge with shut-off cock, (2) external relief valves, (2) outlet full port ball valves, (2) check valves, (1) 2 1/2" SS case, liquid filled pressure gauge with shut-off cock. All equipment mounted on formed steel unit base with drip pan.


## System Options: Check all that apply

Rupture basin leak switch		4" SS liquid filled gauge ILO 2 1/2"	
Duplex Strainer ILO (2) Simplex		Gauge snubber	
Strainer DP switch/indicator		TEFC motors	
Discharge flow switch		Flex hose conn (suc/disch)	
Discharge pressure switch		Unit vibration isolation mounts	


# Model HX1860 Duplex Pump Set



Standard with simplex strainer



Options Shown: Duplex Strainer, DP switch,  
 Flow Switch, and Basin Switch



The type X system is provided as a complete mechanical assembly with all piping complete as shown. Unit will be hydrostatically tested and fluorescent leak inspected at the factory. The system requires wiring and controls by others.

## Performance Data & Equipment Information

Pump Flow Rate (gph)	1860	Motor HP	3	Volts *	460	Inlet conn. size	2 1/2"
Discharge Press. (psig)	100	RPM	1150	Phase	3	Outlet conn. size	2"
Estimated System Weight (lbs.)	780			Motor Full Load Amps @ 460 Volts *	4.8		

\* All standard single and three phase voltage available upon request.


## Standard Equipment

(2) pumps, (2) ODP motors, (2) permanent alignment brackets with flexible couplings, (2) simplex inlet basket strainers, 1/16" perforated baskets, (2) inlet full port ball valves, (2) 2 1/2" SS case, liquid filled compound gauge with shut-off cock, (2) external relief valves, (2) outlet full port ball valves, (2) check valves, (1) 2 1/2" SS case, liquid filled pressure gauge with shut-off cock. All equipment mounted on formed steel unit base with drip pan.


## System Options: Check all that apply

Rupture basin leak switch		4" SS liquid filled gauge ILO 2 1/2"	
Duplex Strainer ILO (2) Simplex		Gauge snubber	
Strainer DP switch/indicator		TEFC motors	
Discharge flow switch		Flex hose conn (suc/disch)	
Discharge pressure switch		Unit vibration isolation mounts	


# Model HX2940 Duplex Pump Set



Standard with simplex strainer



Options Shown: Duplex Strainer, DP switch,  
 Flow Switch, and Basin Switch



The type X system is provided as a complete mechanical assembly with all piping complete as shown. Unit will be hydrostatically tested and fluorescent leak inspected at the factory. The system requires wiring and controls by others.

## Performance Data & Equipment Information

Pump Flow Rate (gph)	2940	Motor HP	5	Volts *	460	Inlet conn. size	2 1/2"
Discharge Press. (psig)	100	RPM	1150	Phase	3	Outlet conn. size	2"
Estimated System Weight (lbs.)	1000		Motor Full Load Amps @ 460 Volts *		7.6		

\* All standard single and three phase voltage available upon request.




## Standard Equipment

(2) pumps, (2) ODP motors, (2) permanent alignment brackets with flexible couplings, (2) simplex inlet basket strainers, 1/16" perforated baskets, (2) inlet full port ball valves, (2) 2 1/2" SS case, liquid filled compound gauge with shut-off cock, (2) external relief valves, (2) outlet full port ball valves, (2) check valves, (1) 2 1/2" SS case, liquid filled pressure gauge with shut-off cock. All equipment mounted on formed steel unit base with drip pan.

## System Options: Check all that apply

Rupture basin leak switch		4" SS liquid filled gauge ILO 2 1/2"	
Duplex Strainer ILO (2) Simplex		Gauge snubber	
Strainer DP switch/indicator		TEFC motors	
Discharge flow switch		Flex hose conn (suc/disch)	
Discharge pressure switch		Unit vibration isolation mounts	

# Model LX0040 Duplex Pump Set



The type X system is provided as a complete mechanical assembly with all piping complete as shown. Unit will be hydrostatically tested and fluorescent leak inspected at the factory. The system requires wiring and controls by others.

## Performance Data & Equipment Information

Pump Flow Rate (gph)	40	Motor HP	1/3	Volts *	115	Inlet conn. size	1/2"
Discharge Press. (psig)	50	RPM	1750	Phase	1	Outlet conn. size	1/2"
Estimated System Weight (lbs.)	300			Motor Full Load Amps @ 115 Volts *	7.2		

\* All standard single and three phase voltage available upon request.




## Standard Equipment

(2) pumps, (2) ODP motors, (2) permanent alignment brackets with flexible couplings, (2) simplex inlet basket strainers, 1/16" perforated baskets, (2) inlet full port ball valves, (2) 2 1/2" SS case, liquid filled compound gauge with shut-off cock, (2) external relief valves, (2) outlet full port ball valves, (2) check valves, (1) 2 1/2" SS case, liquid filled pressure gauge with shut-off cock. All equipment mounted on formed steel unit base with drip pan.

## System Options: Check all that apply

Rupture basin leak switch		4" SS liquid filled gauge ILO 2 1/2"	
Duplex Strainer ILO (2) Simplex		Gauge snubber	
Strainer DP switch/indicator		TEFC motors	
Discharge flow switch		Flex hose conn (suc/disch)	
Discharge pressure switch		Unit vibration isolation mounts	

# Model LX0084 Duplex Pump Set



The type X system is provided as a complete mechanical assembly with all piping complete as shown. Unit will be hydrostatically tested and fluorescent leak inspected at the factory. The system requires wiring and controls by others.

## Performance Data & Equipment Information

Pump Flow Rate (gph)	84	Motor HP	1/3	Volts *	115	Inlet conn. size	1/2"
Discharge Press. (psig)	50	RPM	1750	Phase	1	Outlet conn. size	1/2"
Estimated System Weight (lbs.)	300			Motor Full Load Amps @ 115 Volts *	7.2		

\* All standard single and three phase voltage available upon request.




## Standard Equipment

(2) pumps, (2) ODP motors, (2) permanent alignment brackets with flexible couplings, (2) simplex inlet basket strainers, 1/16" perforated baskets, (2) inlet full port ball valves, (2) 2 1/2" SS case, liquid filled compound gauge with shut-off cock, (2) external relief valves, (2) outlet full port ball valves, (2) check valves, (1) 2 1/2" SS case, liquid filled pressure gauge with shut-off cock. All equipment mounted on formed steel unit base with drip pan.

## System Options: Check all that apply

Rupture basin leak switch		4" SS liquid filled gauge ILO 2 1/2"	
Duplex Strainer ILO (2) Simplex		Gauge snubber	
Strainer DP switch/indicator		TEFC motors	
Discharge flow switch		Flex hose conn (suc/disch)	
Discharge pressure switch		Unit vibration isolation mounts	

# Model LX0162 Duplex Pump Set



The type X system is provided as a complete mechanical assembly with all piping complete as shown. Unit will be hydrostatically tested and fluorescent leak inspected at the factory. The system requires wiring and controls by others.

## Performance Data & Equipment Information

Pump Flow Rate (gph)	162	Motor HP	1/3	Volts *	115	Inlet conn. size	3/4"
Discharge Press. (psig)	50	RPM	1750	Phase	1	Outlet conn. size	1/2"
Estimated System Weight (lbs.)	300			Motor Full Load Amps @ 115 Volts *	7.2		

\* All standard single and three phase voltage available upon request.

## Standard Equipment




(2) pumps, (2) ODP motors, (2) permanent alignment brackets with flexible couplings, (2) simplex inlet basket strainers, 1/16" perforated baskets, (2) inlet full port ball valves, (2) 2 1/2" SS case, liquid filled compound gauge with shut-off cock, (2) external relief valves, (2) outlet full port ball valves, (2) check valves, (1) 2 1/2" SS case, liquid filled pressure gauge with shut-off cock. All equipment mounted on formed steel unit base with drip pan.

## System Options: Check all that apply

Rupture basin leak switch		4" SS liquid filled gauge ILO 2 1/2"	
Duplex Strainer ILO (2) Simplex		Gauge snubber	
Strainer DP switch/indicator		TEFC motors	
Discharge flow switch		Flex hose conn (suc/disch)	
Discharge pressure switch		Unit vibration isolation mounts	



# Model LX0234 Duplex Pump Set



The type X system is provided as a complete mechanical assembly with all piping complete as shown. Unit will be hydrostatically tested and fluorescent leak inspected at the factory. The system requires wiring and controls by others.

## Performance Data & Equipment Information

Pump Flow Rate (gph)	234	Motor HP	1/3	Volts *	115	Inlet conn. size	3/4"
Discharge Press. (psig)	50	RPM	1750	Phase	1	Outlet conn. size	1/2"
Estimated System Weight (lbs.)	300			Motor Full Load Amps @ 115 Volts *	7.2		

\* All standard single and three phase voltage available upon request.


## Standard Equipment

(2) pumps, (2) ODP motors, (2) permanent alignment brackets with flexible couplings, (2) simplex inlet basket strainers, 1/16" perforated baskets, (2) inlet full port ball valves, (2) 2 1/2" SS case, liquid filled compound gauge with shut-off cock, (2) external relief valves, (2) outlet full port ball valves, (2) check valves, (1) 2 1/2" SS case, liquid filled pressure gauge with shut-off cock. All equipment mounted on formed steel unit base with drip pan.


## System Options: Check all that apply

Rupture basin leak switch		4" SS liquid filled gauge ILO 2 1/2"	
Duplex Strainer ILO (2) Simplex		Gauge snubber	
Strainer DP switch/indicator		TEFC motors	
Discharge flow switch		Flex hose conn (suc/disch)	
Discharge pressure switch		Unit vibration isolation mounts	


# Model LX0312 Duplex Pump Set



Standard with simplex strainer



Options Shown: Duplex Strainer, DP switch,  
 Flow Switch, and Basin Switch



The type X system is provided as a complete mechanical assembly with all piping complete as shown. Unit will be hydrostatically tested and fluorescent leak inspected at the factory. The system requires wiring and controls by others.

## Performance Data & Equipment Information

Pump Flow Rate (gph)	312	Motor HP	1/3	Volts *	115	Inlet conn. size	1"
Discharge Press. (psig)	50	RPM	1750	Phase	1	Outlet conn. size	3/4"
Estimated System Weight (lbs.)	300		Motor Full Load Amps @ 115 Volts *		7.2		

\* All standard single and three phase voltage available upon request.


## Standard Equipment

(2) pumps, (2) ODP motors, (2) permanent alignment brackets with flexible couplings, (2) simplex inlet basket strainers, 1/16" perforated baskets, (2) inlet full port ball valves, (2) 2 1/2" SS case, liquid filled compound gauge with shut-off cock, (2) external relief valves, (2) outlet full port ball valves, (2) check valves, (1) 2 1/2" SS case, liquid filled pressure gauge with shut-off cock. All equipment mounted on formed steel unit base with drip pan.


## System Options: Check all that apply

Rupture basin leak switch		4" SS liquid filled gauge ILO 2 1/2"	
Duplex Strainer ILO (2) Simplex		Gauge snubber	
Strainer DP switch/indicator		TEFC motors	
Discharge flow switch		Flex hose conn (suc/disch)	
Discharge pressure switch		Unit vibration isolation mounts	


# Model LX0360 Duplex Pump Set



Standard with simplex strainer



Options Shown: Duplex Strainer, DP switch,  
 Flow Switch, and Basin Switch



The type X system is provided as a complete mechanical assembly with all piping complete as shown. Unit will be hydrostatically tested and fluorescent leak inspected at the factory. The system requires wiring and controls by others.

## Performance Data & Equipment Information

Pump Flow Rate (gph)	360	Motor HP	1/2	Volts *	460	Inlet conn. size	1"
Discharge Press. (psig)	50	RPM	1150	Phase	3	Outlet conn. size	3/4"
Estimated System Weight (lbs.)	370			Motor Full Load Amps @ 460 Volts *	1.4		

\* All standard single and three phase voltage available upon request.


## Standard Equipment

(2) pumps, (2) ODP motors, (2) permanent alignment brackets with flexible couplings, (2) simplex inlet basket strainers, 1/16" perforated baskets, (2) inlet full port ball valves, (2) 2 1/2" SS case, liquid filled compound gauge with shut-off cock, (2) external relief valves, (2) outlet full port ball valves, (2) check valves, (1) 2 1/2" SS case, liquid filled pressure gauge with shut-off cock. All equipment mounted on formed steel unit base with drip pan.


## System Options: Check all that apply

Rupture basin leak switch		4" SS liquid filled gauge ILO 2 1/2"	
Duplex Strainer ILO (2) Simplex		Gauge snubber	
Strainer DP switch/indicator		TEFC motors	
Discharge flow switch		Flex hose conn (suc/disch)	
Discharge pressure switch		Unit vibration isolation mounts	


# Model LX0600 Duplex Pump Set



Standard with simplex strainer



Options Shown: Duplex Strainer, DP switch,  
 Flow Switch, and Basin Switch



The type X system is provided as a complete mechanical assembly with all piping complete as shown. Unit will be hydrostatically tested and fluorescent leak inspected at the factory. The system requires wiring and controls by others.

## Performance Data & Equipment Information

Pump Flow Rate (gph)	600	Motor HP	1	Volts *	460	Inlet conn. size	1"
Discharge Press. (psig)	50	RPM	1750	Phase	3	Outlet conn. size	3/4"
Estimated System Weight (lbs.)	350			Motor Full Load Amps @ 460 Volts *	2.1		

\* All standard single and three phase voltage available upon request.


## Standard Equipment

(2) pumps, (2) ODP motors, (2) permanent alignment brackets with flexible couplings, (2) simplex inlet basket strainers, 1/16" perforated baskets, (2) inlet full port ball valves, (2) 2 1/2" SS case, liquid filled compound gauge with shut-off cock, (2) external relief valves, (2) outlet full port ball valves, (2) check valves, (1) 2 1/2" SS case, liquid filled pressure gauge with shut-off cock. All equipment mounted on formed steel unit base with drip pan.


## System Options: Check all that apply

Rupture basin leak switch		4" SS liquid filled gauge ILO 2 1/2"	
Duplex Strainer ILO (2) Simplex		Gauge snubber	
Strainer DP switch/indicator		TEFC motors	
Discharge flow switch		Flex hose conn (suc/disch)	
Discharge pressure switch		Unit vibration isolation mounts	


# Model LX0780 Duplex Pump Set



Standard with simplex strainer



Options Shown: Duplex Strainer, DP switch,  
 Flow Switch, and Basin Switch



The type X system is provided as a complete mechanical assembly with all piping complete as shown. Unit will be hydrostatically tested and fluorescent leak inspected at the factory. The system requires wiring and controls by others.

## Performance Data & Equipment Information

Pump Flow Rate (gph)	780	Motor HP	1	Volts *	460	Inlet conn. size	1 1/2"
Discharge Press. (psig)	50	RPM	1150	Phase	3	Outlet conn. size	1 1/4"
Estimated System Weight (lbs.)	470			Motor Full Load Amps @ 460 Volts *	2.1		

\* All standard single and three phase voltage available upon request.


## Standard Equipment

(2) pumps, (2) ODP motors, (2) permanent alignment brackets with flexible couplings, (2) simplex inlet basket strainers, 1/16" perforated baskets, (2) inlet full port ball valves, (2) 2 1/2" SS case, liquid filled compound gauge with shut-off cock, (2) external relief valves, (2) outlet full port ball valves, (2) check valves, (1) 2 1/2" SS case, liquid filled pressure gauge with shut-off cock. All equipment mounted on formed steel unit base with drip pan.


## System Options: Check all that apply

Rupture basin leak switch		4" SS liquid filled gauge ILO 2 1/2"	
Duplex Strainer ILO (2) Simplex		Gauge snubber	
Strainer DP switch/indicator		TEFC motors	
Discharge flow switch		Flex hose conn (suc/disch)	
Discharge pressure switch		Unit vibration isolation mounts	


# Model LX1110 Duplex Pump Set



Standard with simplex strainer  
 Inlet  
 Outlet



Options Shown: Duplex Strainer, DP switch,  
 Flow Switch, and Basin Switch  
 Inlet  
 Outlet



The type X system is provided as a complete mechanical assembly with all piping complete as shown. Unit will be hydrostatically tested and fluorescent leak inspected at the factory. The system requires wiring and controls by others.

## Performance Data & Equipment Information

Pump Flow Rate (gph)	1110	Motor HP	1	Volts *	460	Inlet conn. size	1 1/2"
Discharge Press. (psig)	50	RPM	1150	Phase	3	Outlet conn. size	1 1/4"
Estimated System Weight (lbs.)	610			Motor Full Load Amps @ 460 Volts *	2.1		

\* All standard single and three phase voltage available upon request.


## Standard Equipment

(2) pumps, (2) ODP motors, (2) permanent alignment brackets with flexible couplings, (2) simplex inlet basket strainers, 1/16" perforated baskets, (2) inlet full port ball valves, (2) 2 1/2" SS case, liquid filled compound gauge with shut-off cock, (2) external relief valves, (2) outlet full port ball valves, (2) check valves, (1) 2 1/2" SS case, liquid filled pressure gauge with shut-off cock. All equipment mounted on formed steel unit base with drip pan.


## System Options: Check all that apply

Rupture basin leak switch		4" SS liquid filled gauge ILO 2 1/2"	
Duplex Strainer ILO (2) Simplex		Gauge snubber	
Strainer DP switch/indicator		TEFC motors	
Discharge flow switch		Flex hose conn (suc/disch)	
Discharge pressure switch		Unit vibration isolation mounts	


# Model LX1260 Duplex Pump Set



Standard with simplex strainer



Options Shown: Duplex Strainer, DP switch,  
 Flow Switch, and Basin Switch



The type X system is provided as a complete mechanical assembly with all piping complete as shown. Unit will be hydrostatically tested and fluorescent leak inspected at the factory. The system requires wiring and controls by others.

## Performance Data & Equipment Information

Pump Flow Rate (gph)	1260	Motor HP	1 1/2	Volts *	460	Inlet conn. size	1 1/2"
Discharge Press. (psig)	50	RPM	1750	Phase	3	Outlet conn. size	1 1/4"
Estimated System Weight (lbs.)	470			Motor Full Load Amps @ 460 Volts *	3.0		

\* All standard single and three phase voltage available upon request.




## Standard Equipment

(2) pumps, (2) ODP motors, (2) permanent alignment brackets with flexible couplings, (2) simplex inlet basket strainers, 1/16" perforated baskets, (2) inlet full port ball valves, (2) 2 1/2" SS case, liquid filled compound gauge with shut-off cock, (2) external relief valves, (2) outlet full port ball valves, (2) check valves, (1) 2 1/2" SS case, liquid filled pressure gauge with shut-off cock. All equipment mounted on formed steel unit base with drip pan.

## System Options: Check all that apply

Rupture basin leak switch		4" SS liquid filled gauge ILO 2 1/2"	
Duplex Strainer ILO (2) Simplex		Gauge snubber	
Strainer DP switch/indicator		TEFC motors	
Discharge flow switch		Flex hose conn (suc/disch)	
Discharge pressure switch		Unit vibration isolation mounts	

# Model LX1800 Duplex Pump Set



The type X system is provided as a complete mechanical assembly with all piping complete as shown. Unit will be hydrostatically tested and fluorescent leak inspected at the factory. The system requires wiring and controls by others.

## Performance Data & Equipment Information

Pump Flow Rate (gph)	1800	Motor HP	2	Volts *	460	Inlet conn. size	2"
Discharge Press. (psig)	50	RPM	1750	Phase	3	Outlet conn. size	1 1/2"
Estimated System Weight (lbs.)	550			Motor Full Load Amps @ 460 Volts *	3.4		

\* All standard single and three phase voltage available upon request.

## Standard Equipment


(2) pumps, (2) ODP motors, (2) permanent alignment brackets with flexible couplings, (2) simplex inlet basket strainers, 1/16" perforated baskets, (2) inlet full port ball valves, (2) 2 1/2" SS case, liquid filled compound gauge with shut-off cock, (2) external relief valves, (2) outlet full port ball valves, (2) check valves, (1) 2 1/2" SS case, liquid filled pressure gauge with shut-off cock. All equipment mounted on formed steel unit base with drip pan.

## System Options: Check all that apply


Rupture basin leak switch		4" SS liquid filled gauge ILO 2 1/2"	
Duplex Strainer ILO (2) Simplex		Gauge snubber	
Strainer DP switch/indicator		TEFC motors	
Discharge flow switch		Flex hose conn (suc/disch)	
Discharge pressure switch		Unit vibration isolation mounts	




# Model LX2040 Duplex Pump Set



Standard with simplex strainer



Options Shown: Duplex Strainer, DP switch,  
 Flow Switch, and Basin Switch



The type X system is provided as a complete mechanical assembly with all piping complete as shown. Unit will be hydrostatically tested and fluorescent leak inspected at the factory. The system requires wiring and controls by others.

## Performance Data & Equipment Information

Pump Flow Rate (gph)	2040	Motor HP	2	Volts *	460	Inlet conn. size	2 1/2"
Discharge Press. (psig)	50	RPM	1150	Phase	3	Outlet conn. size	2"
Estimated System Weight (lbs.)	750			Motor Full Load Amps @ 460 Volts *	3.4		

\* All standard single and three phase voltage available upon request.


## Standard Equipment

(2) pumps, (2) ODP motors, (2) permanent alignment brackets with flexible couplings, (2) simplex inlet basket strainers, 1/16" perforated baskets, (2) inlet full port ball valves, (2) 2 1/2" SS case, liquid filled compound gauge with shut-off cock, (2) external relief valves, (2) outlet full port ball valves, (2) check valves, (1) 2 1/2" SS case, liquid filled pressure gauge with shut-off cock. All equipment mounted on formed steel unit base with drip pan.


## System Options: Check all that apply

Rupture basin leak switch		4" SS liquid filled gauge ILO 2 1/2"	
Duplex Strainer ILO (2) Simplex		Gauge snubber	
Strainer DP switch/indicator		TEFC motors	
Discharge flow switch		Flex hose conn (suc/disch)	
Discharge pressure switch		Unit vibration isolation mounts	


# Model LX3060 Duplex Pump Set



Standard with simplex strainer



Options Shown: Duplex Strainer, DP switch,  
 Flow Switch, and Basin Switch



The type X system is provided as a complete mechanical assembly with all piping complete as shown. Unit will be hydrostatically tested and fluorescent leak inspected at the factory. The system requires wiring and controls by others.

## Performance Data & Equipment Information

Pump Flow Rate (gph)	3060	Motor HP	3	Volts *	460	Inlet conn. size	2 1/2"
Discharge Press. (psig)	50	RPM	1150	Phase	3	Outlet conn. size	2"
Estimated System Weight (lbs.)	880			Motor Full Load Amps @ 460 Volts *	4.8		

\* All standard single and three phase voltage available upon request.

## Standard Equipment

(2) pumps, (2) ODP motors, (2) permanent alignment brackets with flexible couplings, (2) simplex inlet basket strainers, 1/16" perforated baskets, (2) inlet full port ball valves, (2) 2 1/2" SS case, liquid filled compound gauge with shut-off cock, (2) external relief valves, (2) outlet full port ball valves, (2) check valves, (1) 2 1/2" SS case, liquid filled pressure gauge with shut-off cock. All equipment mounted on formed steel unit base with drip pan.

## System Options: Check all that apply

Rupture basin leak switch		4" SS liquid filled gauge ILO 2 1/2"	
Duplex Strainer ILO (2) Simplex		Gauge snubber	
Strainer DP switch/indicator		TEFC motors	
Discharge flow switch		Flex hose conn (suc/disch)	
Discharge pressure switch		Unit vibration isolation mounts	